SARP | 100/7.62L

REMOTELY OPERATED
STABILIZED WEAPON PLATFORM

#LandandWeaponSystems



LOW SILHOUTTE AND WEIGHT
AUTOMATIC TARGET TRACKING
AUTOMATIC BALISTIC CALCULATION
HIGH HIT PROBABILITY
COMPATIBLE WITH UNMANNED PLATFORMS

aselsan

SARP | 100/7.62L

REMOTELY OPERATED STABILIZED WEAPON PLATFORM

The compact design of the system proves SARP 100/7.62L is a perfect match for integration onto tactical vehicles, fixed surveillance posts and towers. Depending on the operational requirements, SARP 100/7.62L can be equipped with 5.56 and 7.62 mm machine guns. Through its extensive surveillance and remote control capabilities, SARP 100/7.62L enhances situational awareness of the gunner in his proximity while the vulnerability to attacks is decreased drastically.

Advanced Features

- Shoot-on-the-move capability for stationary and moving targets
- Day and night imaging
- Automatic target tracking
- Automatic ballistic calculation
- Laser Range Finder for accurate ballistics
- Computer based fire control functions
- Fired rounds counter
- Last ammunition warning
- Manuel operation and control
- Complies with MIL-STD-810 for environmental conditions
- Capability for integration to external sensors, radars and command and control systems
- Inhanced User Interface
- Remote control and firing capabilities
- Reconnaissance, detection and track of targets (passive)
- Movement and Fire Fobidden Zone

Options

- Armor protection STANAG 4569
- Operable from far distances with wireless communication capability

Payload Options

- IR laser pointer

Technical Specifications

Weapon Options(Main Weapon)

- 5,56 mm : FN M249 Machine Gun
- 7,62 mm : PMT 7.62 Machine Gun
  FN MAG58 Machine Gun
  M240 Machine Gun
  PKT Machine Gun

Movement

- Elevation : -30° / +75°
- Azimuth : n x 360°

Weight and Height

- Weight : 110-130 kg (w/o gun & ammunition)
- Height : 550-650 mm

Camera and Sensors

- CCTV, IR Camera and Laser Range Finder (An advanced and modular sensor suit -day, night, LRF- enables unique and tailorable situational awareness)



Specifications are subject to change without any notice. | All tolerances are within ±10%.

SST - SARP 100/7.62L - 07.2025

CALL CENTER +90 850 360 10 30 | P: +90 (312) 592 10 00 F: +90 (312) 354 13 02 | sstmarketing@aselsan.com

aselsan