SARP | 200/12.7

STABILIZED ADVANCED REMOTE
WEAPON PLATFORM

#LandandWeaponSystems



AUTOMATIC TARGET TRACKING
AUTOMATIC BALISTIC CALCULATION
HIGH HIT PROBABILITY
ENHANCED USER INTERFACE
UNDER ARMOR AMMO RELOADING

aselsan

SARP | 200/12.7

STABILIZED ADVANCED REMOTE WEAPON PLATFORM

The design of the system proves SARP 200/12.7 is a perfect match for integration onto tactical vehicles, fixed surveillance posts and towers. Depending on the operational requirements, SARP 200/12.7 can be equipped 12.7 mm machine gun, 7.62 mm machine gun, 40 mm automatic grenade launcher. Through its extensive surveillance and remote control capabilities, SARP 200/12.7 enhances situational awareness of the gunner in his proximity while the vulnerability to attacks is decreased drastically.

Advanced Features

- Shoot-on-the-move capability for stationary and moving targets
- Day and night imaging
- Automatic target tracking
- Automatic ballistic calculation
- Laser Range Finder for accurate ballistics
- Computer based fire control functions
- Fired rounds counter
- Last ammunition warning
- Manuel operation and control
- Complies with MIL-STD-810 for environmental conditions
- Capability for integration to external sensors, radars and command and control systems
- Inhanced User Interface
- Remote control and firing capabilities
- Reconnaissance, detection and track of targets (passive)
- Movement and Fire Fobidden Zone

Options

- Armor protection STANAG 4569
- Operable from far distances with wireless communication capability
- Under and/or above armor ammunition reloading
- Picture-in-Picture

Payload Options

- Smoke grenade launcher
- IR laser pointer
- Acoustic Gunshot Detection Systems
- 40 mm Airburst Ammunition Integration

Technical Specifications

Weapon Options (Main Weapon)

- 7,62 mm : PMT 7.62 Machine Gun
  FN MAG58 Machine Gun
  M240 Machine Gun
  PKM Machine Gun
- 12,7 mm : PMT 12.7 Machine Gun
  M2HB Machine Gun
  NSV Machine Gun
  MT12-QCB Machine Gun
- 40 mm : MK19 Mod3 Automatic Grenade Launcher

Movement

- Elevation : -30° / +60°
- Azimuth : n x 360°

Weight and Height

- Weight : 235 kg (w/o gun & ammunition)
- Height : 800 mm

Camera and Sensors

- CCTV, IR Camera and Laser Range Finder (an advanced and modular sensor suit -day, night, LRF- enables unique and tailorable situational awareness)



Specifications are subject to change without any notice. | All tolerances are within ±10%.

SST - SARP 200/12.7 - 07.2025

CALL CENTER +90 850 360 10 30 | P: +90 (312) 592 10 00 F: +90 (312) 354 13 02 | sstmarketing@aselsan.com

aselsan